



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

ACORA-KSNS

INTERCHANGE STANDARD	Parker 4000, DNP PDV/PDS, Faster NV/NS, Holmbury DIN, Dixon AG; Stucchi IRV/IR, Aeroquip FD42, Snap Tite 60/21, Safeway S20, Tomco P/C
APPLICATION	Series couplings have their main application in agricultural equipment, Mobile and construction equipment.
CHARACTERISTICS	According to the standard ISO5675. Available in the version DN13 with poppet and ball valve, The KSNV-08M is interchangeable with KSA/KSW-V-08M. Locking ball system allows quick connection&disconnection. Bidirectional flow

Specification:

	Standard: ISO 5675 Materials: zinc-plated carbon steel body Seals: standard in nitrile NBR. On request FKM, EPDM seals Back-up ring: PTFE Working temperature: with standard seals -25°C + 125°C
--	--

CH&J	ISO	L1	L2	L3	Ø D	S1	S2	T
ACORA-KSNS 1/2	12.5	93	68.5	46.5	38	27	27	1/2" NPT