



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

CONCORD

Tube	Black EPDM
Reinforcement	High tensile steel cords
Cover	Red EPDM - Heat, abrasion and ozone resistant, pin pricked
Application	Saturated steam; widely use in refineries, shipyards and petrochemical plants
Temperature	-40° C to + 210°C and up to +232°C for intermittent periods

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
1/2	13	25	6	17	250	170	2250	130	0.55	60
3/4	19	32	6.5	17	250	170	2250	190	0.719	60
1	25	38	6.5	17	250	170	2250	250	0.892	60
1 1/2	38	54	8	17	250	170	2250	385	1.708	30