



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

FLX2005

**Tube** Silicone coated glass fiber fabric.**Cover** Silicone coated glass fiber fabric.**Reinforcement** Spiral Spring steel wire. Glass fiber cord.**Application** Suction hose: For transmission hot air, chemical fumes and industrial fumes – For printing machines, blowers – For exhausting gas, engine construction, engine warming, aircraft construction and military construction.**Temperature** -70°C - +260°C. Shorttime to +280°C**Features** Double-layer of silicone coated glass fiber fabric. Extremely good heat resistance. Leak-proof. Smooth interior. Highly flexible. Small bending radius. Kink-proof.

ID		OD (mm)	WALL THICKNESS (mm)	BENDING RADIUS (mm)	WORK PRESSURE (PSI)	VACUUM PRESSURE (PSI)	LENGHT (m)
Inch.	mm.						
3.1/2	89	94	0.4	141	30	5.51	4
4	102	107	0.4	160	27.55	5.08	4
6	152	158	0.4	237	18.85	2.61	4
8	203	209	0.4	313	11.6	1.45	4