



IMPORTADORA

**CHIRIBOGA
& JARA S.A.**

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

H100

WOG LOCK ON HOSE WP 20 BAR / 300 PSI

Tube	Black NBR
Reinforcement	High tensile synthetic yarn
Cover	Black textile braid - weather and ozone resistant
Application	Delivery of fuel and gas
Temperature	-30° C to + 90°C

I.D.		O.D		WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm		Bar	Psi	Bar	Psi			
1/4	6.0	12.0	3.0	20	300	60	900	45	0.139	100	
5/16	8.0	14.0	3.0	20	300	60	900	65	0.141	100	
3/8	10.0	16.0	3.0	20	300	60	900	75	0.185	100	
1/2	13.0	19.0	3.0	20	300	60	900	90	0.233	100	
5/8	16.0	23.0	3.5	20	300	60	900	115	0.324	100	
3/4	19.0	26.0	3.5	20	300	60	900	135	0.370	100	