



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

H201

FUEL HOSE WP 20 BAR / 300 PSI**Tube** Black NBR**Reinforcement** High tensile synthetic yarn**Cover** Black NBR/CR - weather, ozone and hydrocarbon resistant**Application** Delivery of fuel and gas**Temperature** -30° C to + 90°C

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
1/4	6.0	13.0	3.5	20	300	60	900	51	0.175	100
5/16	8.0	15.0	3.5	20	300	60	900	67	0.195	100
3/8	10.0	17.0	3.5	20	300	60	900	83	0.210	100
1/2	13.0	20.0	3.5	20	300	60	900	107	0.267	100
5/8	16.0	26.0	5.0	20	300	60	900	131	0.490	100
3/4	19.0	29.0	5.0	20	300	60	900	155	0.556	100
1	25.0	36.5	5.5	20	300	60	900	203	0.684	100