



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

Serie A100 / Serie P3

MANGUERA ACERO INOXIDABLE SERIE A100**ESPECIFICACIONES**

CERTIFICADO ISO 10380 (Click para Descargar)

(http://chiribogayjara.com/ckfinder/userfiles/files/DNV%20Certificate%20of%20Conformity_C751077%20Rev_%200%20(1).pdf)

SERIE A100 - ANULAR INOXIDABLE PASO ESTÁNDAR

DISPONIBLE EN ACERO INOXIDABLE AISI 321; AISI 316L

RANGO DE TEMPERATURA: -200°C HASTA +550°C

(PULG.)	NUM.PARTE AEROFLEX	MALLAS TRENZADAS	D.E. MM	D.I. MM	RADIO MAXIMO DE CURVATURA MM		PRESION @ 23° C (bar/cm2)			PESO (kg/mtr)
					ESTATICA	DINAMICA	MAX. DE TRABAJO	MAX. TEST	RUPTURA	
1/4"	A10016006	0	9.6				12	18	140	0.076
	A100161401006	1	10.8	6.2	25	85	120	180	480	0.150
	A100162401006	2	12.0				192	288	768	0.24
5/16"	A10016008	0	12.1				10	15	120	0.087
	A100161401008	1	13.3	8.2	32	125	100	150	400	0.167
	A100162401008	2	14.5				160	240	640	0.260
3/8"	A10016010	0	14.3				9	14	100	0.112
	A100161401010	1	15.5	10.3	38	140	90	135	360	0.215
	A100162401010	2	16.7				144	216	576	0.333
1/2"	A10016012	0	16.7				9	14	90	0.118
	A100161401012	1	17.9	12.2	45	140	80	128	320	0.240
	A100162401012	2	19.1				128	192	512	0.379
5/8"	A10016016	0	21.6				8	12	85	0.195
	A100161401016	1	23.0	16.2	58	160	70	105	280	0.400
	A100162401016	2	24.4				112	168	448	0.630
3/4"	A10016020	0	26.8				4	6	65	0.250
	A100161401020	1	28.3	20.2	70	170	64	96	256	0.495
	A100162401020	2	29.8				102	154	410	0.765
1"	A10016025	0	32.2				3	5	55	0.355
	A100161401025	1	33.7	25.4	85	190	50	75	200	0.630
	A100162401025	2	35.2				80	120	320	0.930
1.1/4"	A10016032	0	41.1				2	3	50	0.445
	A100161401032	1	42.7	34.3	105	260	40	60	160	0.847
	A100162401032	2	44.3				64	96	256	1.281
1.1/2"	A10016040	0	49.5				1	2	45	0.682
	A100161401040	1	51.1	40.1	130	300	35	53	140	1.172
	A100162401040	2	52.7				56	84	224	1.694
2"	A10016050	0	60.3				1	2	45	0.880
	A100161401050	1	62.3	50.3	160	320	30	45	120	1.606
	A100162401050	2	64.3				48	72	192	2.383