



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

SUPER RESISTANT CONCRETE PUMP HOSE ASSEMBLY

Tube	UPE and SBR & NR synthetic rubber
Reinforcement	2~4 layers of steel cord
Cover	SBR & NR synthetic rubber and UPE
Application	Apply to construction machinery like pump truck to delivery concrete. Its service life is several times more than average products in the market, and the high saturation characteristic of UPE (Ultra High Molecular Weight Polyethylene Inner Tube) meaning that this product would not react with the alkaline substance in the concrete
Assembly length	3" x 7mts with HD fittings
Type of Coupling	HD
Temperature	-29°C~ +80°C (-20.2°F~+176°F)

I.D.		O.D.	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
3	76	98	22	85	1232	213	3089	800	4.75	7