



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

UFR/L-04



FLUID	Compressed air
CONSTRUCTION	Piston type regulation
MATERIAL	BODY:Aluminum die-cast, BOWL:Polyacarbonate
FILTER ELEMENT	Standard:40 micron, Optional:5 micron
OPER.PRESSURE RANGE	0.5-9.9 kgf/cm ²
MAX.PRESSURE	9.9 kgf/cm ²
MAX.FLOW RATE	2600 l/ min
TEMPERATURE RANGE	-10`C-60`C
LUBRICATION OIL	ISO-VG32 (recommended)
BOWL CAPACITY	Filter bowl 105c.c. , Lubricator bowl 125c.c.
DRAIN	Semi-automatic drain (below 0.5kgf/cm ²)
WEIGHT	1480 g
ACCESORIES	Gauge, Bracket set.

'Optional auto-drain order add letter "D"

*Optional acid & alkali cup-add letter "A"