



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

W-AGUAD

DELIVERY OF AIR & WATER HOSE WP 10 BAR / 150 PSI

Tube	Black SBR
Reinforcement	High tensile textile cords
Cover	Black EPDM/SBR - abrasion and ozone resistant
Application	Delivery of air and water
Temperature	-30° C to + 80°C

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
1 1/4	32.0	42.0	5.0	10	150	30	450	384	1.200	60
1 1/2	38.0	48.0	5.0	10	150	30	450	456	1.375	60
2	51.0	63.0	6.0	10	150	30	450	612	1.850	60
2 1/2	63.0	79.0	8.0	10	150	30	450	756	2.250	60
3	76.0	92.0	8.0	10	150	30	450	912	3.600	60
4	102.0	118.0	8.0	10	150	30	450	1224	4.750	60
6	152.4	172.0	9.8	10	150	30	450	-	-	60