



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

W-AIRE 300

COMPRESSED AIR HOSE YELLOW 20 BAR / 300 PSI**Tube** Black SBR/NBR**Reinforcement** High tensile synthetic yarn**Cover** Black EPDM/SBR - abrasion and ozone resistant**Application** Duty transfer of air and water. Compressed air in mines, construction, jackhammer.**Temperature** -30°C to +80°C

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
1/4	6	14	4.0	20	300	60	900	50	0.210	100
5/16	8	16	4.0	20	300	60	900	66	0.261	100
3/8	9.5	18	4.25	20	300	60	900	82	0.317	100
1/2	13	22	4.5	20	300	60	900	106	0.440	150
3/4	19	29	5.0	20	300	60	900	154	0.630	150
1	25	36	5.5	20	300	60	900	202	0.855	150
1.1/4	32	44	6.0	20	300	60	900	-	-	60
1.1/2	38	54	8.0	20	300	60	900	350	1.930	60
2	51	67	8.0	20	300	60	900	495	2.591	60
3	76	92	8.0	20	300	60	900	750	2.65	60
4	102	118	8.0	20	300	60	900	1000	3.81	60