



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

W-LYNX

BULK MATERIAL DELIVERY HOSE WP 10 BAR / 150 PSI**Tube** Static-Resistant Gum Rubber Blend - high abrasion 1/4" Wall Thickness**Reinforcement** High tensile textile cords**Cover** Black conductive EPDM/NR -high abrasion resistant**Application**

Dry bulk cement discharge hose is designed specifically for the transfer of dry cement, lime, pebble, and other abrasive materials. This hose has a two-ply fabric reinforcement and a specially formulated static resistant natural rubber lining. The lining comes in 1/4" thickness. The cover is also composed of an abrasion and ozone resistant rubber blend.

Temperature -30° C to + 80°C

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
4	102	120	9	10	150	30	450	1090	4.567	60