



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

W-MULTI300

**MULTIPURPOSE HOSE WP 20 BAR / 300 PSI OIL RESISTANT**

Tube	Black NBR
Reinforcement	High tensile synthetic yarn
Cover	Red NBR/CR-abrasion, ozone and hydrocarbon resistant
Application	Delivery of fuel, oil, compressed air and water.
Temperature	-30° C to + 80° C

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
1/4	6.0	13.0	3.5	20	300	30	900	51	0.164	200
3/8	10.0	17.0	3.5	20	300	30	900	83	0.255	200
1/2	13.0	20.0	3.5	20	300	30	900	107	0.307	100
3/4	19.0	29.0	5.0	20	300	30	900	155	0.616	100
1	25.0	36.0	5.5	20	300	30	900	203	0.789	100
1-1/4	32.0	44.0	6.0	20	300	30	900	-	-	60
1-1/2	38	54	8.0	20	300	30	900	-	-	60