



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (<http://chiribogayjara.com>)

W-SANDBLAST

SANDBLAST HOSE WP 12 BAR / 175 PSI

Tube	Black conductive SBR/NR - high abrasion resistant
Reinforcement	High tensile textile cords
Cover	Black conductive EPDM/NR -abrasion and ozone resistant pin pricked
Application	Conveyance of sand and steel grit
Temperature	-30°C to +80°C

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
1.1/4	32.0	48.0	8.0	12	175	36	520	260	1.20	60
1.1/4	32.0	54.0	11.0	12	175	36	520	320	0.75	60
1.1/2	38.0	60.0	11.0	12	175	36	520	380	1.78	60