



IMPORTADORA

**CHIRIBOGA**  
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

**GYE:** (593-4) 6005004 - (593-4) 6005005

**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

W-TANK 150



## PETROLEUM SUCTION AND DELIVERY HOSE WP 10 BAR/150 PSI

<b>Tube</b>	Black Nitrile synthetic rubber RMA Class A (High Oil Resistance)
<b>Reinforced</b>	High tensile textile cords with embedded steel helix wire for electric continuity.
<b>Cover</b>	Black (red stripe) synthetic rubber (oil resistant); wrapped finish.
<b>Application</b>	WINFLEX TANK 150 is for use in tank truck and in-plant operations. Can transfer petroleum products up to 50% aromatic content. Capable of reaching a maximum operating pressure of 150 PSI and temperatures up to +80°C as well.
<b>Temperature</b>	-20°C to + 80°C
<b>Safety factor</b>	3:1

I.D.		O.D.		WALL THICKNESS Mm	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		VACUUM (MAX)	BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm		Bar	Psi	Bar	Psi				
6	152	175	11.5	10	150	30	450	80	885	8.205	30	
8	203	228	12.5	10	150	30	450	70	1200	14.496	24	