



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

W-TANK 300

PETROLEUM SUCTION AND DELIVERY HOSE WP 20 BAR/300 PSI

Tube	Black Nitrile synthethic rubber RMA Class A (High Oil Resistance)
Reinforcement	Hight tensile textile cords with embedded steel helix wire.
Cover	Black (blue stripe) synthethic rubber, resistant to ozone, abrasion and hydrocarbons. Wrapped finished.
Application	Be applicable to suction and discharge gasoline, kerosene, diesel, engine oil, heavy oil and other mineral oils
Temperature	-35°F to 180°F (-37°C to 80°C)
Safety Factor	3:1

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		VACUUM (MAX)	BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	%	Mm	Kg/m	M
2	51	65	7.	20	300	60	900	94	210	1.901	60
3	76	92	8	20	300	60	900	83	415	3.112	60
4	102	122	10	20	300	60	900	83	620	5.154	60
6	152	177	12.5	20	300	60	900	78	985	8.935	30