



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

W-WILDCAT

HOT AIR BLOWER HOSE WP 10 BAR / 150 PSI

Tube

Black EPDM, resistant to hot air.

Reinforcement

Multi plies of synthetic high tensile textile with 2 helix wire providing high crush and kink resistant hose capability.

Cover

Black EPDM Rubber, Flat Corrugated cover. Pin pricked.

Application

A compressor hose for use with silo vehicles as a connecting hose between the discharge compressor and the silo.

Temperature

-30°C to +150°C (Heat resistant intermittent service to 170°C)

Safety Factor

3:01

1 Pascal=1Bar-1Mpa=10Bar-1Bar

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT APROX	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
3	76	92	8	10	150	30	450	330	3.160	40