



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

W4SH

Tube	Oil resistant synthetic rubber
Reinforcement	Four spirail high tensile steel wire
Cover	Abrasion and weather resistant synthetic rubber
Application	Used to convey mineral oil based hydraulic oil, oil and water emulsion and aqueous glycol solutions
Temperature	-40°C to +100°C
Safety Factor	4:1

I.D.		WORKING PRESSURE		TEST PRESSURE		BURST PRESSURE		BEND RADIUS	WEIGHT (APPROX)
DN	INCH	BAR	PSI	BAR	PSI	BAR	PSI	mm	Kg/m
19	3/4	420	6090	840	12180	1680	24360	280	1.4
25	1	380	5510	760	11020	1520	22040	340	2
31	1.1/4	340	5000	680	10000	1360	20000	460	2.55
38	1.1/2	290	4205	580	8410	1160	16820	560	3.05
51	2	250	3625	500	7250	1000	14500	700	4.35

1 Bar= 14.5 PSI