



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

WR15

Tube:	Oil resistant synthetic rubber
Reinforcement:	Four or six spiral high tensile steel wire
Cover:	Oil and weather resistant synthetic rubber
Application:	Used to convey mineral oil based hydraulic oil, and water emulsion and aqueous glycol solutions
Temperature:	-40°C to +121°C
Safety Factor:	4:1

I.D		WORKING PRESSURE		TEST PRESSURE		BURST PRESSURE		BEND RADIUS	WEIGHT (APPROX)
DN	INCH	BAR	PSI	BAR	PSI	BAR	PSI	mm	Kg/m
25	1	420	6090	840	12180	1680	24360	330	2.1
32	1-1/4	420	6090	840	12180	1680	24360	445	3.9
38	1-1/2	420	6090	840	12180	1680	24360	530	4.65
50	2	420	6090	840	12180	1680	24360	635	6.58

*1Bar= 1Pascal

*1Bar= 14.5PSI

*1Mpa=10Bar