



[CONTINENTAL] LPG DELIVERY PRO350

Marking: 1" (25.4mm) LPG Delivery Pro™ CGA Type 1 LPG-Hose Issue No. E- 8167 350 PSI (2.4 MPa) Max WP. **Made in U.S.A.**

Applications

LPG Deliver Pro™ is for residential and commercial delivery/transfer of liquid propane gas, LPG dispensing and LPG portable heaters. Excellent cold weather flexibility, a smooth cover for low drag resistance, and a low extraction tube to reduce contamination. The hose meets **UL, CGA** and **DOT** requirements. Additional applications require prior approval. Not for LPG appliances or other consumer applications.

Specifications

- **Construction Tube:** Nitrile (NBR)
- **Cover:** Synthetic rubber, Pin-Pricked
- **Reinforcement:** 4 Layers, Spiral, Textile
- **Design Factor:** 5:1
- **Coupling:** Please refer to LPG Delivery Pro™ crimp specs and use ContiTech approved Male NPT fittings.
- **Temperature Range:** -40°F to 180°F (-40°C to 82°C)

Technical Data Imperial

Ch&J Code	InnerØ (in)	OuterØ (in)	Weight (lbs/ft)	WorkingPressure (PSI)
LPG PRO 1/2	1/2	0.93	0.25	350
LPG PRO 3/4	3/4	1.23	0.38	350
LPG PRO 1	1	1.49	0.51	350
LPG PRO 1-1/4	1-1/4	1.80	0.67	350
LPG PRO 1-1/2	1-1/2	2.04	0.78	350

Technical Data Metric

Ch&J Code	InnerØ (mm)	OuterØ (mm)	Weight (kg/m)	WorkingPressure (MPa)
LPG PRO 1/2	12.70	23.60	0.37	2.41
LPG PRO 3/4	19.10	31.20	0.57	2.41
LPG PRO 1	25.40	37.80	0.76	2.41
LPG PRO 1-1/4	31.80	45.60	1.00	2.41

LPG PRO 1-1/2	38.10	51.80	1.16	2.41
---------------	-------	-------	------	------

CERTIFICATE OF COMPLIANCE (<http://chiribogayjara.com/ckfinder/userfiles/files/LPG%20UL%20Cert.pdf>)



(<http://chiribogayjara.com/ckfinder/userfiles/files/LPG%20UL%20Cert.pdf>)

(CLICK PARA DESCARGAR) (<http://chiribogayjara.com/ckfinder/userfiles/files/LPG%20UL%20Cert.pdf>)