IMPORTADORA
CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador
GYE: (593-4) 6005004 - (593-4) 6005005
GYE: (593-4) 3082583
www.chiribogayjara.com (http://chiribogayjara.com)



FLX2005

Tube	Silicone coated glass fiber fabric.
Cover	Silicone coated glass fiber fabric.
Reinforcement	Spiral Spring steel wire. Glass fiber cord.
Application	Suction hose: For transmission hot air, chemical fumes and industrial fumes – For printing machines, blowers – For exhausting gas, engine construction, engine warming, aircraft construction and military construction.
Temperature	-70°C - +260°C. Shortime to+280°C
Features	Double-layer of silicone coated glass fiber fabric. Extremely good heat resistance. Leak-proof. Smooth interior. Highly flexible. Small bending radius. Kink-proof.

ID		OD	WALL	BENDING	WORK	VACUUM	LENGHT
Inch.	mm.	(mm)	THICKNESS (mm)	RADIUS (mm)	PRESSURE (PSI)	PRESSURE (PSI)	(m)
3.1/2	89	94	0.4	141	30	5.51	4
4	102	107	0.4	160	27.55	5.08	4
6	152	158	0.4	237	18.85	2.61	4
8	203	209	0.4	313	11.6	1.45	4

www.chiribogayjara.com