IMPORTADORA
CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador
GYE: (593-4) 6005004 - (593-4) 6005005
GYE: (593-4) 3082583
www.chiribogayjara.com (http://chiribogayjara.com)



H100

WOG LOCK ON HOSE WP 20 BAR / 300 PSI

Tube	Black NBR
Reinforcement	High tensile synthetic yarn
Cover	Black textile braid - weather and ozone resistant
Application	Delivery of fuel and gas
Temperature	-30° C to + 90°C

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	**Mm**	**Mm**	**Mm**	**Bar**	**Psi**	**Bar**	**Psi**	**Mm**	**Kg/m**	**M**
1/4	6.0	12.0	3.0	20	300	60	900	45	0.139	100
5/16	8.0	14.0	3.0	20	300	60	900	65	0.141	100
3/8	10.0	16.0	3.0	20	300	60	900	75	0.185	100
1/2	13.0	19.0	3.0	20	300	60	900	90	0.233	100
5/8	16.0	23.0	3.5	20	300	60	900	115	0.324	100
3/4	19.0	26.0	3.5	20	300	60	900	135	0.370	100

www.chiribogayjara.com