









## KIT JET-WASH HOSE MALE NPT FITTINGS

www.chiribTubegay Black synthetic rubber

Two braids of high tensile wire. Reinforcement

Cover Black Synthetic rubber

Standard-duty use on hot and cold water high-pressure cleaning

Specially compounded cover to handle pressure washer environment.

-40° C to + 150°C equipment. Extremely flexible, lightweight and easy to handle. Tube Application

WMW'CUIL

Temperature

<sub>vw.chi</sub>		DESCRIPTION	
	JWHN-05X10M	5/16 X 10M (NPT 3/8") W.P. 6000 PSI, GREY	
	JWHN-05X12M	5/16 X 12M (NPT 3/8") W.P. 6000 PSI, GREY	
	JWHN-05X15M	5/16 X 15M (NPT 3/8") W.P. 6000 PSI, GREY	
	JWHN-06X10M	3/8 X 10M (NPT 3/8") W.P. 6000 PSI, BLUE	on con
	JWHN-06X12M	3/8 X 10M (NPT 3/8") W.P. 6000 PSI, BLUE  3/8 X 12M (NPT 3/8") W.P. 6000 PSI, BLUE	ara.co
	JWHN-06X15M	10/0 X 13W (W 1 5/0 ) W.I . 0000 1 3I, DEDE	
	ribogayja	ira.com	
chi	ribogaylo		