



IMPORTADORA

**CHIRIBOGA
& JARA S.A.**

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)



Manguera PU Material

Construction

Polyurethane combines the best properties of both plastic and rubber. It offers abrasion and tear resistance, high tensile and elongation values, and low compression set. Polyurethane is naturally flexible and exhibits virtually unlimited flexural abilities. It has exceptional resistance to most gasolines, oils, kerosene, and other petroleum-based chemicals.

Application

Delivery hose usage, Automobile industry, Construction industry, Industry robots and pneumatic tools, Transport water and other liquid, Hydraulic machinery, Electronics industry

Temperature

-40° a 70°C

CH&J CODE	ID	OD	WP		BP		BENDING RADIUS	LENGTH
	mm	mm	PSI	BAR	PSI	BAR	mm	m/roll
NA-0420	2	4	145	10	464	32	8	200
NA-0640	4	6	116	8	348	24	15	200
NA-0850	5	8	145	10	464	32	20	100
NA-1065	6.5	10	116	8	348	24	25	100
NA-1280	8	12	116	8	348	24	35	100
NA-1612	12	16	116	8	348	24	70	100

CH&J CODE	OD	WP		BP		BENDING RADIUS	LENGTH
	INCH	PSI	BAR	PSI	BAR	INCH	m/roll
NA-1/4	1/4	116	8	348	24	15	200
NA-3/8	3/8	116	8	348	24	25	100
NA-1/2	1/2	116	8	348	24	35	100