



PUDUCT

- Tube** Top grade of ester base Polyurethane.
- Cover** Top grade of ester base Polyurethane.
- Reinforcement** Copper plated steel wire.
- Application** Ideally as suction and transport hose for abrasive solids such as dust, powders, wood chips, granulates, oil and fuel etc. Also very suitable for ventilation system and industrial vaccum cleaner.
- Temperature** -40°C to +90°C (Short time to 125°C)
- Features** Very nice looking with transparent wall and cooper plated steel wire. Extremely abrasion-resistant. High tensile and burst strength and tearing resistant. Could be static electricity conductive by grounding the steel wire. Resistant to oil and fuel. Extremely flexible and compressible. Small bending radius. Free of plasticizer. Free of halogen. Various colors are available. Different wall thickness are available. Comply to RoHS

I.D.	I.D.	WALL	BEND	WORKING	VACUUM	LENGTH
HOSE	HOSE	THICKNESS	RADIUS	PRESSURE	PRESSURE	
(inch)	(mm)	(mm)	(mm)	(PSI)	(PSI)	(m)
1.1/2	38	0.6	54	23	6	15
2	51	0.6	69	20	4	15
3	76	0.6	102	14	3	15
4	102	0.6	166	11	2	15
6	152	0.6	241	4	2	15
8	203	0.6	318	3	1	15