IMPORTADORA
CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador
**GYE:** (593-4) 6005004 - (593-4) 6005005
**GYE:** (593-4) 3082583
www.chiribogayjara.com (http://chiribogayjara.com)




## SUPER RESISTANT CONCRETE PUMP HOSE ASSEMBLY

| | |
|---|---|
| **Tube** | UPE and SBR & NR synthetic rubber |
| **Reinforcement** | 2~4 layers of steel cord |
| **Cover** | SBR & NR synthetic rubber and UPE |
| **Application** | Apply to construction machinery like pump truck to delivery concrete. Its service life is several times more than average products in the market, and the high saturation characteristic of UPE (Ultra High Molecular Weight Polyethylene Inner Tube) meaning that this product would not react with the alkaline substance in the concrete |
| **Assembly length** | 3” x 7mts with HD fittings |
| **Type of Coupling** | HD |
| **Temperature** | -29°C~ +80°C (-20.2°F~+176°F) |

| I.D. | | O.D. | WALL THICKNESS | WORKING PRESSURE (MAX) | | BURST PRESSURE (MIN) | | BEND RADIUS (MIN) | WEIGHT (APPROX) | STANDARD LENGTH |
|---|---|---|---|---|---|---|---|---|---|---|
| Inch | Mm | Mm | Mm | Bar | Psi | Bar | Psi | Mm | Kg/m | M |
| 3 | 76 | 98 | 22 | 85 | 1232 | 213 | 3089 | 800 | 4.75 | 7 |

www.chiribogayjara.com