



IMPORTADORA

CHIRIBOGA & JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)

TJ2D EXTRA ABRASION RESISTANT FRAS JACK HOSE TWO WIRE BRAID



RECOMMENDED FOR:

Hydraulic Jack applications requiring a light weight, small outside diameter hose. The very high abrasion resistant properties of the DIEHARD cover extend the life of the hose when it is subjected to the abrasion that may cause the premature failure of standard hoses.

PERFORMANCE:

Meets or Exceeds the Performance Requirements of: Materials Handling Institute specification IJ 100 (July 1979) for hydraulic hose and assemblies used with jacking systems.

TUBE:

Black, oil resistant synthetic rubber.

REINFORCEMENT:

Two braids of high tensile steel wire.

COVER:

DIEHARD™ Black, oil and extra abrasion resistant synthetic rubber. Flame Resistant, Anti-Static (FRAS) & MSHA compliant. Highly visible layline branding for easy and permanent identification. No skiving required with T2000 Series Crimp Couplings.

FRAS - FLAME RESISTANCE AND ANTI-STATIC:

DIEHARD™ complies with Flame Resistant and Electrical Resistance (Anti-Static) requirements of Australian Standard AS 2660 and Methods of Test AS 1180.10B and 13A. Meets Flame Resistant Designation "U.S. MSHA" of the US Department of Labor, Mine Safety and Health Administration.

TEMPERATURE RANGE:

From -40°C to +49°C (-40°F to +120°F).
For water, emulsions etc. see page 58.

WORKING PRESSURE:

Specification IJ 100 (July 1979) is based on 2:1 minimum burst to maximum working pressure safety factor and is suitable for 700 bar/10,000 psi use in hydraulic jack applications ONLY.

COUPLINGS:

NON-SKIVE ONE-PIECE CRIMP

T2000 Series (sizes -04 to -06) pages 187 to 232. Assembly Instructions pages 478.

TJ2D - DIEHARD JACK HOSE		NOMINAL HOSE ID		NOMINAL HOSE OD		MAXIMUM WORKING PRESSURE		MINIMUM BURST PRESSURE		MINIMUM BEND RADIUS		AVERAGE WEIGHT		COUPLING SERIES
PART NO	HOSE SIZE	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	ONE PIECE
TJ24D	6 -04	6,6	1/4	14,9	0.59	700	10000	1400	20000	100	3.9	0.35	0.24	T2000
TJ26D	10 -06	9,8	3/8	18,9	0.74	700	10000	1400	20000	130	5.0	0.51	0.34	T2000

NOTE: Ensure rated Working Pressure of chosen End Style meets or exceeds the 700 bar/10,000 psi Maximum Working Pressure of TJ2D hose.

For hydraulic jack applications, RYCO recommends the use of 3/8" NPTF Male Extended Couplings.

TJ24D: Part No. T2091-0406 One-Piece Crimp. Use of RYCO 750 Spring Guards at each end of the hose assembly is also recommended.

TJ26D: Part No. T2091-0606 One-Piece Crimp. Use of a Bend Restrictor device at each end of the hose assembly is also recommended.

Refer to the latest RYCO Crimp Charts for crimp diameter and mark lengths.

TJ2D

CHIRIBOGA & JARA S.A.