



IMPORTADORA

**CHIRIBOGA
& JARA S.A.**

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com**TP7**
SPIDERLINE
R7 HOSE

RYCO SPIDERLINE TP7

RECOMMENDED FOR:

High pressure hydraulic oil lines; pilot lines; greasing and lubrication lines; and some pneumatic and water lines. Suitable for use with mineral, vegetable and most ester based hydraulic fluids. Suitable for use with some gases, fluids and chemicals. Cover is perforated (pin-pricked) for use with air and gases.

RYCO SPIDERLINE hose is lighter weight, has a more compact outside diameter and is less than half the minimum bend radius of wire braided rubber hose. Smooth inner tube for high flow rate; and smooth, easily cleaned cover.

The synthetic and aramid fibre reinforcement gives SPIDERLINE hose excellent corrosion and fatigue resistance plus low elongation at maximum dynamic working pressure.

PERFORMANCE:

Meets or Exceeds the Performance Requirements of:
AS 3791 100R7, EN 855 TYPE R7, ISO 3949, SAE 100R7.

TUBE:

White, oil resistant seamless thermoplastic (Polyester).

REINFORCEMENT:

One or two braids of synthetic fibre.

COVER:

Black, oil and abrasion resistant thermoplastic (Polyurethane). Cover is perforated (pin-pricked).

TEMPERATURE RANGE:

From -40°C to +100°C (-40°F to +212°F).

Air & Water +70 °C (+158 °F).

For water, emulsions etc. see page 58.

WORKING PRESSURE:

Maximum working pressures are based on 4:1 safety factor (maximum working pressure to minimum burst pressure).

COUPLINGS:**NON-SKIVE ONE-PIECE CRIMP**

TP000 Series (sizes -03 to -16) pages 304 to 316.

Assembly Instructions pages 478.

TP7 - SPIDERLINE HOSE																
PART NO	HOSE SIZE		NOMINAL HOSE ID		NOMINAL HOSE OD		MAXIMUM WORKING PRESSURE		MINIMUM BURST PRESSURE		MINIMUM BEND RADIUS		AVERAGE WEIGHT		COUPLING SERIES ONE PIECE	
Hose	DN	Dash	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	NON-SKIVE	
TP73	5	-03	5,0	3/16	9,6	0.38	210	3000	840	12000	25	1.0	0,06	0.04	TP000	
TP74	6	-04	6,5	1/4	12,2	0.48	210	3000	840	12000	35	1.4	0,10	0.07	TP000	
TP75	8	-05	8,1	5/16	14,3	0.56	190	2700	760	10800	45	1.8	0,13	0.09	TP000	
TP76	10	-06	9,7	3/8	16,0	0.63	160	2300	640	9200	55	2.2	0,15	0.10	TP000	
TP78	12	-08	13,0	1/2	20,3	0.80	140	2000	560	8000	75	3.0	0,22	0.15	TP000	
TP712	19	-12	19,5	3/4	27,1	1.07	90	1300	360	5200	140	5.5	0,34	0.23	TP000	
TP716	25	-16	25,9	1	34,0	1.34	70	1000	280	4000	190	7.5	0,46	0.31	TP000	

Refer to the latest RYCO Crimp Charts for crimp diameter and mark lengths.

TP7

CHIRIBOGA & JARA S.A.