



IMPORTADORA

**CHIRIBOGA
& JARA S.A.**

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (<http://chiribogayjara.com>)



TWIN R7

- Tube:** Nylon 11
- Reinforcement:** One layer of synthetic fiber braid
- Cover:** Oil-resistant, aging-resistant, weather-resistant black polyurethane (perforated)
- Application:** It is suitable for conveying petroleum-based hydraulic oil and water-based hydraulic oil. It can be used as a lubrication line and blowout preventer control line. It is widely used in hydraulic elevators and agricultural and construction machinery. The low effusion rate of this hose makes it ideally suited for CO2 and Nitrogen. Perforated cover permits breathing, eliminating condensation and blistering.
- Temperature:** -40°C to +93°C
- Safety Factor:** 4:1

I.D		WORKING PRESSURE		TEST PRESSURE		BURST PRESSURE		BEND RADIUS	WEIGHT (APPROX)
DN	INCH	BAR	PSI	BAR	PSI	BAR	PSI	mm	Kg/m
6	1/4	255	3260	510	6520	1020	13040	100	0.180
10	3/8	155	2250	310	4500	620	9000	125	0.310
13	1/2	140	2030	280	4060	560	8120	180	0.448