



W-AGUAD

## DELIVERY OF AIR & WATER HOSE WP 10 BAR / 150 PSI

<b>Tube</b>	Black SBR
<b>Reinforcement</b>	High tensile textile cords
<b>Cover</b>	Black EPDM/SBR - abrasion and ozone resistant
<b>Application</b>	Delivery of air and water
<b>Temperature</b>	-30° C to + 80°C

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
1 1/4	32.0	42.0	5.0	10	150	30	450	384	1.200	60
1 1/2	38.0	48.0	5.0	10	150	30	450	456	1.375	60
2	51.0	63.0	6.0	10	150	30	450	612	1.850	60
2 1/2	63.0	79.0	8.0	10	150	30	450	756	2.250	60
3	76.0	92.0	8.0	10	150	30	450	912	3.600	60
4	102.0	118.0	8.0	10	150	30	450	1224	4.750	60
6	152.4	172.0	9.8	10	150	30	450	-	-	60