



W-AGUAD

DELIVERY OF AIR & WATER HOSE WP 10 BAR / 150 PSI

| | |
|----------------------|---|
| Tube | Black SBR |
| Reinforcement | High tensile textile cords |
| Cover | Black EPDM/SBR - abrasion and ozone resistant |
| Application | Delivery of air and water |
| Temperature | -30° C to + 80°C |

| I.D. | | O.D | WALL THICKNESS | WORKING PRESSURE (MAX) | | BURST PRESSURE (MIN) | | BEND RADIUS (MIN) | WEIGHT (APPROX) | STANDARD LENGTH |
|-------|-------|-------|----------------|------------------------|-----|----------------------|-----|-------------------|-----------------|-----------------|
| Inch | Mm | Mm | Mm | Bar | Psi | Bar | Psi | Mm | Kg/m | M |
| 1 1/4 | 32.0 | 42.0 | 5.0 | 10 | 150 | 30 | 450 | 384 | 1.200 | 60 |
| 1 1/2 | 38.0 | 48.0 | 5.0 | 10 | 150 | 30 | 450 | 456 | 1.375 | 60 |
| 2 | 51.0 | 63.0 | 6.0 | 10 | 150 | 30 | 450 | 612 | 1.850 | 60 |
| 2 1/2 | 63.0 | 79.0 | 8.0 | 10 | 150 | 30 | 450 | 756 | 2.250 | 60 |
| 3 | 76.0 | 92.0 | 8.0 | 10 | 150 | 30 | 450 | 912 | 3.600 | 60 |
| 4 | 102.0 | 118.0 | 8.0 | 10 | 150 | 30 | 450 | 1224 | 4.750 | 60 |
| 6 | 152.4 | 172.0 | 9.8 | 10 | 150 | 30 | 450 | - | - | 60 |