IMPORTADORA
CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador
GYE: (593-4) 6005004 - (593-4) 6005005
GYE: (593-4) 3082583
www.chiribogayjara.com (http://chiribogayjara.com)



W- AIRE 300 PV

COMPRESSED AIR HOSE RED 20 BAR / 300 PSI

Tube	PVC & Rubber Mixed, abrasion, weather and oil resistant.
Reinforcement	High tensile synthetic yarn
Cover	PVC & Rubber Mixed, abrasion, weather and oil resistant.
Application	Medium Duty transfer of air, water, oil and mild chemicals in constructions, mining, industry and other applications.
Temperature	-5°C to +65°C

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
3/8	10	16	3	20	300	60	900	82	0.165	100
1/2	13	19	3	20	300	60	900	106	0.203	100
3/4	19	28	4.5	20	300	60	900	154	0.450	100
1	25	34	4.5	20	300	45	675	202	0.560	100

www.chiribogayjara.com