IMPORTADORA
CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador
GYE: (593-4) 6005004 - (593-4) 6005005
GYE: (593-4) 3082583
www.chiribogayjara.com (http://chiribogayjara.com)



W-FUEL

FUEL HOSE WP 20 BAR / 300 PSI

Tube Black NBR

Reinforcement High tensile synthetic yarn

Cover Red NBR/CR - weather, ozone and hydrocarbon resistant

Application Delivery of fuel and gas

Temperature -30° C to + 90°C

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
1/2	13.0	20.0	3.5	20	300	60	900	107	0.267	100
3/4	19.0	29.0	5.0	20	300	60	900	155	0.556	100
1	25.0	35.5	5.25	20	300	60	900	203	0.684	100

www.chiribogayjara.com