IMPORTADORA
CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador
GYE: (593-4) 6005004 - (593-4) 6005005
GYE: (593-4) 3082583
www.chiribogayjara.com (http://chiribogayjara.com)



W-LYNX

BULK MATERIAL DELIVERY HOSE WP 5 BAR / 75 PSI
BULK MATERIAL DELIVERY HOSE WP 10 BAR / 150 PSI

Tube	Static-Resistant Gum Rubber Blend – high abrasion 13/64" and 9/32" Wall Thickness
Reinforcement	High tensile textile cords
Cover	Black conductive EPDM/NR –high abrasion resistant
Application	Dry bulk cement discharge hose is designed specifically for the transfer of dry cement, lime, pebble, and other abrasive materials. This hose has a two-ply fabric reinforcement and a specially formulated static resistant natural rubber lining. The lining comes in 13/64″ (5mm) and 9/32" (7mm) thickness. The cover is also composed of an abrasion and ozone resistant rubber blend.
Temperature	-30° C to + 80°C

CODE	I.D. HOSE	I.D. HOSE	O.D. HOSE	WALL THICKNESS	WORKING PRESSURE	BURST PRESSURE	ROLL LENGHT
	INCH	MM	MM	(MM)	(PSI)	(PSI)	(MTS)
W-LYNX 4-LF	4"	102	112	5	75	225	60
W-LYNX 4-NLF	4"	102	116	7	150	450	60

www.chiribogayjara.com