



W-MULTI300

MULTIPURPOSE HOSE WP 20 BAR / 300 PSI OIL RESISTANT

Tube	Black NBR
Reinforcement	High tensile synthetic yarn
Cover	Red NBR/CR-abrasion, ozone and hydrocarbon resistant
Application	Delivery of fuel, oil, compressed air and water.
Temperature	-30° C to + 80° C

I.D.		O.D		WALL THICKNESS		WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M		
1/4	6.0	13.0	3.5	20	300	30	900	51	0.164	200		
3/8	10.0	17.0	3.5	20	300	30	900	83	0.255	200		
1/2	13.0	20.0	3.5	20	300	30	900	107	0.307	100		
3/4	19.0	29.0	5.0	20	300	30	900	155	0.616	100		
1	25.0	36.0	5.5	20	300	30	900	203	0.789	100		
1-1/4	32.0	44.0	6.0	20	300	30	900	-	-	60		
1-1/2	38	54	8.0	20	300	30	900	-	-	60		