



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005**GYE:** (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)



W-NT100

Construction

Core, Nylon; Braid, Polyamide Fiber (3/8" and larger sizes only); Jacket, Nylon.

Application

Air brake systems except where temperature exceed +200°F or where battery acid can drip on tubing.

Temperature

-40°C to +93°C

Note1/8", 5/32", 3/16", 1/4" and 5/16", are SAE J844 Type A (not reinforced);
3/8", 1/2", 5/8" and 3/4" are SAE J844 Type B (reinforced).

*Insert not required. Does not meet DOT standards.

CATALOG NUMBER	TUBE O.D.(IN)	TUBE WALL (IN)	MAX.WORK	MIN. BURST	MIN. BEND RADIUS. 70°F INCH	LBS.PER 100Ft.
			PRES. @ 75° PSI	PRES. @ 75° PSI		
NT10002*	1/8(.125)	0.023	150	1000	0.375	0.4
NT10004	1/4(.250)	0.040	150	1200	1.0	1.2
NT10005	5/16(.312)	0.040	150	1000	1.25	1.8
NT10006	3/8(.375)	0.062	150	1400	1.5	2.9
NT10008	1/2(.500)	0.062	150	950	2.0	3.8
NT10010	5/8(.625)	0.092	150	900	2.5	6.8
NT10012	3/4(.750)	0.092	150	800	3.0	8.4