



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)



W-TANK 150 CORRUGATED

PETROLEUM SUCTION AND DELIVERY HOSE WP 10 BAR/150 PSI

Tube Oil-resistance NBR

Reinforced Multiple textile layers with two helix wire

Cover polymer alloy rubber and NBR flat corrugated. Black (red stripe).

Application WINFLEX TANK 150 is for use in tank truck and in-plant operations. Can transfer petroleum products up to 50% aromatic content. Capable of reaching a maximum operating pressure of 150 PSI and temperatures up to +80°C as well.

Temperature -20°C to + 80°C

Safety factor 3 :1

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE		BURST PRESSURE		VACUUM	BEND RADIUS	WEIGHT (APPROX)	STANDARD
				(MAX)	(MIN)	(MAX)	(MIN)	LENGTH			
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	%	Mm	Kg/m	M
1	25	36.2	5.6	10	150	30	450	100	70	0.874	60
1.1/4	32	43.6	5.8	10	150	30	450	100	90	1.115	60
1.1/2	38	49.6	5.8	10	150	30	450	100	105	1.295	60
2	51	64.4	6.7	10	150	30	450	100	120	1.884	60
2.1/2	64	78	7	10	150	30	450	90	245	2.504	60
3	76	90.4	7.2	10	150	30	450	90	290	3.041	60
4	102	120.4	9.2	10	150	30	450	90	470	5.068	60