IMPORTADORA
CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador
GYE: (593-4) 6005004 - (593-4) 6005005
GYE: (593-4) 3082583
www.chiribogayjara.com (http://chiribogayjara.com)



W-TANK 150

PETROLEUM SUCTION AND DELIVERY HOSE WP 10 BAR/150 PSI

Tube	Black Nitrile synthetic rubber RMA Class A (High Oil Resistance)
Reinforced	High tensile textile cords with embedded steel helix wire for electric continuity.
Cover	Black (red stripe) synthetic rubber (oil resistant); wrapped finish.
Application	WINFLEX TANK 150 is for use in tank truck and in-plant operations. Can transfer petroleum products up to 50% aromatic content. Capable of reaching a maximum operating pressure of 150 PSI and temperatures up to +80°C as well.
Temperature	-20°C to + 80°C
Safety factor	3:1

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		VACUUM (MAX)	BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	%	Mm	Kg/m	M
6	152	175	11.5	10	150	30	450	80	885	8.205	30
8	203	228	12.5	10	150	30	450	70	1200	14.496	24

www.chiribogayjara.com