



W-TANK 300

**PETROLEUM SUCTION AND DELIVERY HOSE WP 20 BAR/300 PSI**

- Tube** Black Nitrile synthetic rubber RMA Class A (High Oil Resistance)
- Reinforcement** High tensile textile cords with embedded steel helix wire.
- Cover** Black (blue stripe) synthetic rubber, resistant to ozone, abrasion and hydrocarbons. Wrapped finished.
- Application** Be applicable to suction and discharge gasoline, kerosene, diesel, engine oil, heavy oil and other mineral oils
- Temperature** -35°F to 180°F (-37°C to 80°C)
- Safety Factor** 3:1

I.D.		O.D.	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		VACUUM (MAX)	BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	%	Mm	Kg/m	M
2	51	65	7	20	300	60	900	94	210	1.901	60
3	76	92	8	20	300	60	900	83	415	3.112	60
4	102	122	10	20	300	60	900	83	620	5.154	60
6	152	177	12.5	20	300	60	900	78	985	8.935	30