



IMPORTADORA

CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 SI 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)



W-UHPH

TUBE: Polyoxymethylene

REINFORCEMENT: Six spiral layers of maximum tensile steel wire

COVER: 1st: Polyamide; 2nd: Polyurethane, abrasion resistant.

Construction and shipbuilding industry (for very high pressure lances with > 300MPa)
Industrial cleaning.

APPLICATION: Hydrodemolition and removal of accumulated dirt and materials.

For working pressure up to 280 MPa (40.600psi)

TEMPERATURE: -10° C up to + 70° C

HOSE SIZE		WORKING PRESSURE		BURST PRESSURE		TEST PRESSURE		BEND RADIUS	WEIGHT (APPROX)
DN	INCH	BAR	PSI	BAR	PSI	BAR	PSI	mm	KG/m
8	1/2	1500	21750	4500	65250	3000	43500	320	1.5

1BAR=1PASCAL

1BAR= 14.5 PSI

1Mpa=10BAR