



**WINFLEX® 1" FOOD PLANT WASHDOWN HOSE 10 BAR / 15**

**W-WASHDOWN**

- Tube:** White heat resistant rubber compound EPDM
- Reinforced:** Two layers of synthetic yarns
- Cover:** White cloth impression, rubber compound EPDM
- Application:** These washdown hose assemblies have an EPDM (ethylene propylene diene monomer) tube and cover that provide excellent resistance to ozone and abrasion and offer good resistance to heat and chemicals. These hoses are designed to convey hot water in washdown and cleanup applications in food-processing plants, dairies, breweries, canneries, creameries and similar industrial locations.
- Temperature:** -40°F to 210°F (-40°C to 99°C)
- Compliance & Restrictions:** This product is not intended for potable water applications (human consumption - drinking and cooking) and has not been designed to be compliant with the "Safe Drinking Water Act" requirements for low lead in potable water applications. This item is for use only in Non-Potable (Non-human consumption) water applications.

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
Inch	Mm	Mm		Bar	Psi	Bar	Psi	Mm	Kg/m	M
1/2	13	20	3.5	10	150	30	450	116	0.306	100
3/4	19	29	5	10	150	30	450	170	0.616	100
1	25	35	5	10	150	30	450	222	0.789	100