IMPORTADORA
CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador
GYE: (593-4) 6005004 - (593-4) 6005005
GYE: (593-4) 3082583
www.chiribogayjara.com (http://chiribogayjara.com)



W-WILDCAT

HOT AIR BLOWER HOSE WP 10 BAR / 150 PSI

Tube	Black EPDM, resistant to hot air.
Reinforcement	Multi plies of synthetic high tensile textile with 2 helix wire providing high crush and kink resistant hose capability.
Cover	Black EPDM Rubber, Flat Corrugated cover. Pin pricked.
Application	A compressor hose for use with silo vehicles as a connecting hose between the discharge compressor and the silo.
Temperature	-30*C to +150*C (Heat resistant intermittent service to 170*C)
Safety Factor	3:01

1Pascal=1Bar-1Mpa=10Bar-1Bar

I.D.		O.D	WALL THICKNESS	WORKING PRESSURE (MAX)		BURST PRESSURE (MIN)		BEND RADIUS (MIN)	WEIGHT APROX	STANDARD LENGTH
Inch	Mm	Mm	Mm	Bar	Psi	Bar	Psi	Mm	Kg/m	M
3	76	92	8	10	150	30	450	330	3.160	40

www.chiribogayjara.com