



IMPORTADORA

CHIRIBOGA & JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador

GYE: (593-4) 6005004 - (593-4) 6005005

GYE: (593-4) 3082583

www.chiribogayjara.com (http://chiribogayjara.com)



W4SP

- TUBE:** Oil resistant synthetic rubber.
REINFORCEMENT: Four spiral high tensile steel wire
COVER: Abrasion and weather resistant synthetic rubber
APPLICATION: Used to convey mineral oil based hydraulic oil, oil and water emulsion and aqueous glycol solution.
TEMPERATURE: -40°C to +121°C
SAFETY FACTOR: 4:01

HOSE SIZE		WORKING PRESSURE		BURST PRESSURE		TEST PRESSURE		BEND RADIUS	WEIGHT (APPROX)
DN	INCH	BAR	PSI	BAR	PSI	BAR	PSI	mm	KG/m
10	3/8	445	6450	1780	25810	890	12905	180	0.75
12	1/2	415	6018	1660	24070	830	12035	230	0.89
16	5/8	350	5075	1400	20300	700	10150	250	1.1
19	3/4	350	5075	1400	20300	700	10150	300	1.5
25	1	280	4060	1120	16240	560	8120	340	2

1BAR=1PASCAL

1BAR= 14.5 PSI

1Mpa=10BAR