



WINPOWER

TANK TRUCK DROP HOSE WITH STATIC GROUNDING WIRE; 40% LIGHTER THAN CONVENTIONAL RUBBER HOSE

Tube	Black Nitrile synthetic static dissipating rubber tube, smooth bore.
Reinforced	One braid of high tensile textile cords with embedded copper wire in the hose wall for electric continuity.
Cover	Rigid PVC helix, corrugated cover.
Application	Used to deliver gasoline, diesel fuel, kerosene and fuel with aromatic contents to 50%.
Features	Lightweight and flexible. External helix provides easy drag.
Temp.Range	-10°F to 140°F (-23°C to 60°C)

Safety factor 3:1

Static wire must be properly imbedded during fitting installation and test to assure proper static grounding of hose to a ground system.

I.D		O.D	WALL THICKNESS	WORKING PRESSURE		BURST PRESSURE		VACUUM	BEND RADIUS	WEIGHT (APPROX)	STANDARD
					(MAX)	(MIN)		(MAX)	(MIN)		LENGTH
INCH	Mm	Mm	Mm	BAR	PSI	BAR	PSI	%	Mm	kg/m	M
3	76	99	11.5	4.5	65	13.5	195	99	196	2.31	30
4	102	127	12.5	4.5	65	13.5	195	99	196	3.88	30