



## WINPOWER

TANK TRUCK DROP HOSE WITH STATIC GROUNDING WIRE; 40% LIGHTER THAN CONVENTIONAL RUBBER HOSE

<b>Tube</b>	Black Nitrile synthetic static dissipating rubber tube, smooth bore.
<b>Reinforced</b>	One braid of high tensile textile cords with embedded copper wire in the hose wall for electric continuity.
<b>Cover</b>	Rigid PVC helix, corrugated cover.
<b>Application</b>	Used to deliver gasoline, diesel fuel, kerosene and fuel with aromatic contents to 50%.
<b>Features</b>	Lightweight and flexible. External helix provides easy drag.
<b>Temp.Range</b>	-10°F to 140°F (-23°C to 60°C)

**Safety factor** 3:1

Static wire must be properly imbedded during fitting installation and test to assure proper static grounding of hose to a ground system.

I.D		O.D	WALL THICKNESS	WORKING PRESSURE		BURST PRESSURE		VACUUM	BEND RADIUS	WEIGHT (APPROX)	STANDARD
					(MAX)	(MIN)		(MAX)	(MIN)		LENGTH
INCH	Mm	Mm	Mm	BAR	PSI	BAR	PSI	%	Mm	kg/m	M
3	76	99	11.5	4.5	65	13.5	195	99	196	2.31	30
4	102	127	12.5	4.5	65	13.5	195	99	196	3.88	30