



**WINPOWER**

TANK TRUCK DROP HOSE WITH STATIC GROUNDING WIRE; 40% LIGHTER THAN CONVENTIONAL RUBBER HOSE

- Tube** Black Nitrile synthetic static dissipating rubber tube, smooth bore.
- Reinforced** One braid of high tensile textile cords with embedded copper wire in the hose wall for electric continuity.
- Cover** Rigid PVC helix, corrugated cover.
- Application** Used to deliver gasoline, diesel fuel, kerosene and fuel with aromatic contents to 50%.
- Features** Lightweight and flexible. External helix provides easy drag.
- Temp. Range** -10°F to 140°F (-23°C to 60°C)
- Safety factor** 3:1

Static wire must be properly imbedded during fitting installation and test to assure proper static grounding of hose to a ground system.

I.D		O.D		WALL THICKNESS	WORKING PRESSURE		BURST PRESSURE		VACUUM (MAX)	BEND RADIUS (MIN)	WEIGHT (APPROX)	STANDARD LENGTH
INCH	Mm	Mm	Mm		BAR	PSI	BAR	PSI				
3	76	99	11.5	4.5	65	13.5	195	99	196	2.31	30	
4	102	127	12.5	4.5	65	13.5	195	99	196	3.88	30	