IMPORTADORA
CHIRIBOGA
& JARA S.A.

Urb. Sta Adriana Mz 3 Sl 7, Av J.T. Marengo Km 5 1/2, Guayaquil-Ecuador
GYE: (593-4) 6005004 - (593-4) 6005005
GYE: (593-4) 3082583
www.chiribogayjara.com (http://chiribogayjara.com)



WINFLEX SAE 100R12

SERIES

Tube	Oil resistant synthetic rubber
Reinforcement	Four spiral high tensile steel wire
Cover	Abrasion and weather resistant synthetic rubber
Application	Used to convey mineral oil based hydraulic oil, oil and water emulsion and aqueous glycol solutions.
Temperature	
Safety Factor	-40°C +121°C 4:1

HOSE SIZE		WORKING PRESSURE		BURST PRESSURE		TEST PRESSURE		BEND RADIUS	WEIGHT (APPROX)
DN	INCH	Bar	Psi	Bar	Psi	Bar	Psi	Mm	Kg/m
31	1-1/4	210	3045	840	12180	420	6090	420	2.80
38	1-1/2	175	2538	700	10150	350	5075	500	3.40
51	2	175	2538	700	10150	350	5075	640	4.25

*1Bar=1Pascal
*1 Bar = 14.5PSI
+1Mpa=10Bar

WR12

CHIRIBOGA & JARA S.A.

www.chiribogayjara.com